

Ground Hog HT1000



6 gpm (22.7 lpm)

SPECIFICATIONS

Operating Pressure:	40,000 psi (2750 bar)
Flow Rate:	Up to 9.2 gpm (34.8 lpm)
Cleaning Capacity:	500-1500 ft. ² /hr (46.45-139.35 m ² /hr)
Cutting Path:	6-14" (15.2 cm - 35.5 cm)

APPLICATIONS

Road Marking Removal	Runway Rubber & Marking Removal
Road Retexturing	Paint Cleaning & Rejuvenation
Surface Preparation	Curing Compound Removal
Airport Apron Cleaning	Car Park Marking Removal

GROUND HOG ADVANTAGES

- ▶ Easily tethers to any of the SH models and can be operated up to 300' (91.4 m) away.
- ▶ Easy removal of crosswalks, turn arrows, gore and chevron areas.
- ▶ Lightest hydraulically rotated floor tool available.
- ▶ The most spray bar and nozzle configurations in the industry.
- ▶ Built in operator safety trigger mechanism.
- ▶ Complete and simultaneous vacuum recovery.

OPTIONS

 <p>High Pressure Hose Up to 300' (91.4 m)</p>	 <p>Spare Parts System Advanced inventory management</p>	 <p>Available Blasting Widths From 6"- 14" (15.2 cm - 35.5 cm)</p>
---	--	---

Manufactured by:



3170 SE Slater Street | Stuart, FL 34997 USA
Phone: (001) 772-223-7393 | Fax: (001) 772-223-5461
waterblastingtechnologies.com

Waterblasting Technologies wants to help you see a live demonstration of the **Stripe Hog Waterblasting System!**

When purchasing waterblasting equipment, it is vitally important that the manufacturer provide you a live demonstration of the equipment either at their headquarters or at a mutually agreeable location so that you can verify for yourself what is being advertised by the manufacturer.

Ground Hog HT1000