

Hog Rider HT2500



6 gpm (22.7 lpm)

SPECIFICATIONS

Operating Pressure:	40,000 psi (2750 bar)
Flow Rate:	Up to 9.2gpm (34.8 lpm)
Cleaning Capacity:	500-1500 ft. ² /hr (46.45-139.35 m ² /hr)
Blasting Widths:	6-36" (15.2-91.4 cm)

APPLICATIONS

Road Marking Removal	Runway Rubber & Marking Removal
Road Retexturing	Paint Cleaning & Rejuvenation
Surface Preparation	Curing Compound Removal
Airport Apron Cleaning	Car Park Marking Removal

HOG RIDER ADVANTAGES

- ▶ Easily tethers to any of the Stripe Hog models and can be operated up to 400' (121 m) away.
- ▶ Easy removal of turn arrows, stop bars, crosswalk lines, and line removal in parking lots and parking garages.
- ▶ Quickly rejuvenate or remove airport gate and apron markings.
- ▶ Efficiently cleans factory, warehouse or hanger floors.
- ▶ Zero-turn tractor

OPTIONS

 <p>High Pressure Hose Up to 400' (121 m)</p>	 <p>Spare Parts System Advanced inventory management</p>	 <p>Available Blasting Widths From 6" - 36" (15.2 cm - 91.4 cm)</p>
--	--	--

Manufactured by:

3170 SE Slater Street | Stuart, FL 34997 USA
Phone: (001) 772-223-7393 | Fax: (001) 772-223-5461
waterblastingtechnologies.com

Waterblasting Technologies wants to help you see a live demonstration of the **Stripe Hog Waterblasting System!**

When purchasing waterblasting equipment, it is vitally important that the manufacturer provide you a live demonstration of the equipment either at their headquarters or at a mutually agreeable location so that you can verify for yourself what is being advertised by the manufacturer.

Hog Rider HT2500